

Edge Shield C6

Compact rugged network security appliance
with 6 x 2.5GbE ports

CODE: H-ES-DIN-C6



A powerful switch for Software-Defined Networking. An advanced probe with state-of-the-art intrusion detection system. Designed for IT and OT.

-  Micro-segmentation and Host isolation
-  Asset and traffic inventory
-  Intrusion Detection System
-  Network probing and visibility

Highlights	
Protect Business Continuity	Data network management aligned with international industrial cybersecurity standards, including IEC 62443, NIS2, NIST, and ISO
High Switching Capability	Fully compliant with SDN standards, integrating network analyzer functions for complete control over data forwarding at the switching level
Regulation Compliance	Implement security systems by defining Security Zones and Conduits without modifying existing IP addresses or VLAN configurations
Cybersecurity functionalities	Integrated Intrusion Detection System (IDS) for both IT and OT traffic, featuring network probes and security level monitoring indicators
High modularity	Available in configurations with 2 SFP+ ports and 8 to 24 Gigabit Ethernet ports
Warranty extension	Option to extend software and hardware warranty coverage up to 5 years
External integration	Full interoperability with third-party products and custom integrations via REST API
White label	Enrich your portfolio with a branded network security solution


Deliver rich functionalities
without breaking compliance

Personalize hardware and
software with your branding

100+ IT/OT standard presets
plus custom extensions

Functionalities & Software Specifications	
Dashboards	Full view for administrators. Simplified dashboard for operational activities
Inventory	Discover devices and assets, creating a network communication matrix within the system
Hosts	Manage individual or grouped devices for advanced micro-segmentation and traffic control
Topology	Intuitive drag-and-drop tool for mapping production processes to discovered devices and communications
Applications	Includes over 100 predefined IT and OT standard applications, with support for custom extensions
Services	Micro-segmented propagation paths between hosts and security zones, defined for each switch port
Profiles	Profiles determine network behavior, enabling the deployment of network services and defining security levels
Monitoring	Easy-to-configure, intuitive indicators to assess the security level of each host and security zone
IDS	Signature-based deep packet inspection for IT and OT anomaly detection, easily customizable and updatable
Log + Alerts	Seamless integration with external log analysis software for system alerts, event logs, and user activity tracking
License	Lifetime license, including one year of software updates, IDS updates, and technical support
Technical support	Specialized support for troubleshooting, system optimization, and integration. Includes documentation, remote assistance, and software updates to ensure Edge SDN Shield remains efficient and secure

Dimensions



Hardware Specifications

Platform	
Processor	Intel Atom® x6413E, 4 cores, 3.0 GHz/1.5 GHz, 9W TDP
System Memory	8GB DDR4 3200 MT/s
Expansion Ports	1x M.2 M Key 2242 SATA SSD
Storage Device	eMMC 5.0 64GB
Cooling	Fanless

I/O	
Ethernet Port (on board)	6x RJ45 2.5GbE Port(s)
USB Port	3x USB 3.2 Gen2x1
Display	1x DP v1.4, resolution up to 4096 x 2160 @ 60Hz
LED Indicators	4 system LEDs (Error/EC Ready/Power/M.2 Storage) and 7 user defined LED

Dimensions, Operation & Certifications	
Form factor	Desktop
Mounting Kit	DIN-Rail mount / Wall mount
Power Connector	1x 3-Pin Terminal Block
Power Supply	Standard: 9-36 VDC, 60W, 24V/2.5A
Size (Width x Length x Height)	100mm (L) x 100mm (W) x 80 mm (H)
Net Weight	1 KG
Operating Environment (Temperature, Humidity)	-20°C ~ 50°C with airflow (LAN speed down to 1G @50°C)
Storage Environment (Temperature, Humidity)	-40°C ~ 85°C
Relative Humidity	5 %~ 95 % (non-condensing)
Vibration	1G, with DIN-Rail (EN 60068-2-6) Wall mount (MIL-STD-810G 514.7C-V Category-4)
Shock	15G with 11ms impulse length, 18 shocks DIN-Rail (EN 60068-2-27) 40G with 11 ms impulse length, 18 shocks Wall mount (EN 60068-2-27)
Degree of Protection	IP30
EMC Standard	EN 61000-6-2, EN 61000-6-4



Address: Via Natalino Corazza 7/7
40128 Bologna (Italy)
www.edge-sdn.com

Copyright 2025, All rights reserved

This document is provided for informational purposes only, its content and product specifications may be subject to change without notice.